

PRO SEAL | 770

PRODUCT DESCRIPTION

WBS Pro-Seal 770 is specifically formulated for oxide coloured cement based construction materials where powdered colour oxide is added to a wet cement mix.

WBS Pro-Seal 770 is a colour stabilising sealer that brings out the natural richer tone of the oxide on a more permanent basis using Moisture Retention Technology.

WBS Pro-Seal 770 is a first coat only product and requires WBS [Pro-Seal 896](#) to be used for the 2nd coat in order to repel oil and stains more successfully.

WBS Pro-Seal 770 is an excellent grouting binder for polishing concrete floors. It UV stabilises the surface and binds fine grinding dust to fill in voids and small pores in the polishing process.

Saves time and money. Seal with WBS [Pro-Seal 896](#) for best results.

USES

First coat sealer for oxide coloured concrete, decorative concrete, new installation natural stone.

Excellent grouting binder when polishing concrete.

Can be used as a pre-sealer to fill voids in highly porous materials prior to sealing with WBS [Pro-Seal 896](#).

FEATURES

- Stabilises the richer natural tone of powder colour oxides.

- Non-Hazardous Material Classification.
- Adds surface flexibility to cement based construction materials.
- Excellent grouting binder for polished concrete.
- Easy to apply / water clean-up.

ENVIRONMENT

All WBS Products are environmentally responsible. WBS Pro-Seal 770 is an environmentally friendly product that is:

- Water-based
- Contains no petroleum solvents or silicone compounds
- Non-hazardous and non-toxic
- 100% biodegradable
- VOC < 2 g/L



APPLICATION

Dilution: WBS Pro-Seal 770 is a highly-concentrated product that requires dilution with water prior to application.

Mix the neat product thoroughly prior to dilution.

Suggested dilution rates are:

1:4 (1 part product : 4 parts water)

Application: Diluted solution should be mixed thoroughly prior to application. Apply using the CSU (Commercial Spray Unit) or suitable spray applicator.

Best applied to a wet/damp surface to help draw product into the surface material. Use white colour of the product as a visual aid to achieve even coverage.

DECORATIVE CONCRETE COLOUR STABILISER

✓ UV Stable ✓ Penetrating ✓ Flexible ✓ Breathable ✓ 100% Acrylic

WATER BASED NON-HAZARDOUS MATERIAL

Polished Concrete Grouting Binder

PRO SEAL | 770

Use a soft bristle broom to sweep out any pools that develop.

Allow to dry clear / 24 hours prior to sealing with WBS Pro-Seal 896.

Polished Concrete Grouting Binder:

Apply diluted solution to the surface during the finer wet grinding stage of the polishing process. Seal with WBS Pro-Seal 896 for best results.

CLEAN UP

Wash all equipment with water after use.



Any overspray on adjacent surfaces such as glass, metal or painted surfaces should be wiped off with a damp rag before the product dries.

CURING

Touch Dry	30-60 minutes
Recoat	24 hours

CONTAINERS

Available in 4L & 15L containers

TECHNICAL DATA

Appearance:	Viscous liquid
Colour:	Milky – White
Odour:	None
pH:	7.5 – 8.5
Water Solubility:	Dispersible
Boiling Point:	100°C
Density:	1.126 ± 0.002
Flash Point:	Not Applicable

COVERAGE

Coverage rates depend on the porosity of the material being sealed. For concrete and similar materials, the coverage rate is:

20 – 25m²/L as neat product

On dense surfaces such as travertine coverage rates are as high as 40m²/L, whereas coverage on very porous materials such as Limestone may be as low as 8-10m²/L.

STORAGE

Store products in a cool dry area, keep product out of direct sunlight.

HEALTH & SAFETY

Keep out of reach of children, wash up any spills by flushing with water, avoid contact with eyes and skin, for professional use only, keep product out of direct sunlight, store in cool dry area.

Classified as Non-Hazardous Material.

TECHNICAL SUPPORT

Water Based Sealers

PO Box 454 Miami
Queensland 4220

Email: info@waterbasedsealers.com.au

Phone: 1800 776 732 (free call in Australia)

SDS sheets available on request

Important:

Information in this documentation is based on our experience with the product. Water Based Sealer's Pty Ltd guarantees the quality of its products but disclaims all liability if the user does not follow the recommendations and conditions of use of the products, especially but not exclusively in the case of faulty application, application by untrained personnel, use of products not compatible with Water Based Sealers products, or adverse weather condition. For more information consult the Safety Data Sheet.

For the most recent version of this document please visit our website:

www.waterbasedsealers.com.au

Made in Australia

Last updated: 19.05.2017

